Flow Visualization of Aircraft in Flight by Means of Background Oriented Schlieren Using Celestial Objects

Michael A. Hill and Edward A. Haering Jr.
NASA Armstrong Flight Research Center
Edwards, CA

Presented By:
Larry Cliatt
NASA Armstrong Flight Research Center

OUTLINE

- Background and Motivation
- BOSCO Concept
  - Background Oriented Schlieren
  - Imaging system
  - Test operation concepts
- Flight Tests
  - CaKEBOS (2015)
  - BOSCO Phase I (2016)
  - BOSCO Phase II (2017)
- Future Work

MOTIVATION

- NASA Commercial Supersonic Technology
  - Desire for a schlieren system for full scale aircraft in flight to visualize shockwaves generated by supersonic aircraft
    - Validate/refine shock modeling for low boom airframe design



BACKGROUND - EXISTING FULL SCALE SCHLIEREN SYSTEMS

Armstrong Flight Research Center

Ground to air solar edge schlieren

- Schlieren for Aircraft in Flight (SAF)
  - NASA, Weinstein 1993
- Ground to Air Schlieren Photography System (GASPS)
  - Digital equivalent of SAF, Metrolaser Inc.





Air to Air Background Oriented Schlieren (AirBOS)

NASA, Heineck, Banks. 2015





Gaps in capability for existing systems

- SAF (Ground to air solar edge)
  - Flow features roughly orthogonal to the solar limb are not imaged. Not a fully 2-D map of air density gradients
  - Resolution of the system is tied to camera frame rate. Increasing the sensor size requires a proportional increase in frame rate. Hardware has an inverse relationship.
- AirBOS
  - Images are mainly plan-form. Aggressive maneuvering is required for side views.
  - Camera aircraft must fly higher altitude than aircraft to be imaged. (low boom demonstrator to fly > 50kft)



BACKGROUND ORIENTED SCHLIEREN CONCEPT

- Visualizes light ray deflections by calculating movement of features in a background
- Provides a full 2-D measurement proportional to the gradient of air density with one image pair
  - With no density gradient, a ray from B will be imaged at point I
  - With a density gradient, a ray from B will be imaged at I', making it appear it is at point B'
  - Finding the difference in location of B and B' gives a measure of ray deflection and therefore density gradient



BOSCO CONCEPT

Background Oriented Schlieren using Celestial Objects (BOSCO)

- Uses narrow band optical filters to give the sun a textured appearance. The texture allows for the BOS method
- Advantages:
  - Full 2D measurement of a BOS system
  - Ability to image from below and to the side of the target aircraft





BOSCO – IMAGING INSTRUMENTATION



BOSCO - PROCESSING

- Optical Flow
  - Developed for computer vision applications in the 1970's/80's
  - Uses the "brightness constancy criterion" – brightness is constant between 2 image pairs, differences in brightness correspond to motion
  - Outputs "flow" vectors, 2D solutions of pixel displacement





BOSCO – IMAGE PROCESSING

A frame before the aircraft eclipses is used for the reference background



Each eclipse frame is aligned with the background frame





Optical Flow is performed on the image pair resulting in a magnitude of pixel displacements



This is repeated for all frames in the eclipse. The median of all the results of all the fames is taken, resulting in the final de-noised schlieren image

BOSCO - TEST OPERATIONS

- Aircraft waypoints were calculated based on time of eclipse, ground position of the imager, and desired altitude of the aircraft.
- Course of the aircraft followed the sun direction across the sky, and flights occurred near the maximum solar elevation angle, to minimize the need for accurate waypoint timing.
- Range from the imager to the aircraft increases as sun elevation decreases and as altitude difference between the imager and aircraft increases



FLIGHT TESTS



- Calcium K Eclipse Background Oriented Schlieren (CAKEBOS)
  - Proof of Concept April 2015
- BOSCO – phase I
  - Tested Improvements in the imaging system. April 2016
- BOSCO – phase II
  - Tested new compact imaging system. April 2017

Calcium-K Eclipse Background Oriented Schlieren (CaKEBOS) April 2015

- Proof of concept test
  - Objective: Demonstrate the feasibility of using Background Oriented Schlieren (BOS) technique in a ground to air system.
  - Used non-optimized hardware already acquired for a previous test
  - Calcium K optical filter





FLIGHT TESTS - CAKEBOS

- Resulting images greatly exceeded expectations
  - System was limited by the digital resolution



Horizontal density gradient

Vertical density gradient

T-38 30000ft AGL, 6.5 mile range, Mach 1.05

BOSCO – Phase I, April 2016

- Success of CaKEBOS allowed for equipment upgrades
  - Higher resolution Camera
    - Photron WX-100: 2048 X 2048 pixels @ 1000 frames/sec
  - Hydrogen alpha telescope
    - More uniform texture distribution
    - Speckle size is smaller and therefore better for BOS
    - Higher contrast



BOSCO SYSTEM (H-A)



- 100 mm f/7 refractor telescope
- H Alpha filter
- 3x Focal extender – Effective focal length: 2100 mm
- Photron WX-100
  - 2048 X 2048 pixels
  - 1000 frames/sec
  - 333 µs integration time
- Manual solar tracking
- Manually triggered at pilot's "mark" call or visual eclipse

BOSCO – 3 IMAGER ARRAY





To increase the field of view of the system, 3 imagers were used in a spaced array in the direction perpendicular to the aircraft course

BOSCO- PHASE I RAW DATA



BOSCO RESULTS

- Imager design improvements verified in BOSCO – Phase I
  - H-α filter provides a better background than CaK
  - Higher digital resolution provided better schlieren image resolution
  - Higher frame rate gave more eclipse frames for improved de-noising





BOSCO-PHASE I RESULTS

- Aircraft banked at sun elevation angle for direct side view
  - Direct side view is of most interest for eventual imaging of low boom demonstrator



3 Image, wide field of view

The top and bottom images in the composite used the older CaKEBOS imagers, resulting in reduced resolution

BOSCO – PHASE I: SUBSONIC RESULTS

T-38 and Beech King Air eclipsing at 10,000ft AGL

- T-38 partially eclipsed the sun resulting in ½ image
- A poor black level calibration on the camera during the King Air pass resulted in reduced quality raw data





BOSCO- PHASE I: EXTENDED AFT VIEW

- By processing many frames after the eclipse, flow features aft of the aircraft can be seen.

- Due to the short wingspan of the T-38, the image of the vortices are quickly Overwhelmed by the engine exhaust more than 5 body lengths aft



BOSCO – Phase II, April 2017

- Test of a new compact imaging system
- Closer range – 2 miles

BOSCO – PHASE II MOTIVATION

Imaging of shocks beneath LBFD aircraft at normal cruise altitude will require very low sun elevation angle.



Low elevation angles will require small differential altitude; future imaging system will be airborne. Camera aircraft will operate roughly 10,000ft horizontal separation from target



BOSCO – PHASE II

New compact imaging system for future airborne use

IDT Camera:
3800 X 2400 pixels
1000 Frames/sec

Nikon Lens
Compact 500mm
Cassegrain lens



H-α filter:
0.5 Angstrom bandpass



BOSCO – PHASE II RAW DATA



BOSCO – PHASE II RESULTS

- Results
  - Images show much more shock detail at close range
  - The increase magnitude of background distortion at the closer range reduces the effectiveness of the optical flow image processing, resulting in noisier results
  - The reduced number of frames to de-noise with also increases noise in final images
    - Will not be an issue with airborne system
  - Compact imaging system performed satisfactory, but needs greater control over image focus



BOSCO- Phase I system

Single element,
fixed focal length
Primary lens

BOSCO- Phase II system

Multi element, compact
Cassegrain primary lens.
Oversensitive focusing
mechanism



CONCLUDING REMARKS AND FUTURE WORK

- Solar chromosphere works well as a background for BOS
  - Both Hydrogen – α line and Calcium-K line produced good results.
    - H- α superior for BOS imaging
- Field of view can be increased with multiple camera array
- Extended view aft of the aircraft can be achieved by processing frames after the eclipse
- Subsonic flow features can be imaged
- Future work
  - Investigate alternate processing methods for close range images
  - Continue development of airborne imaging platform
  - Improve focusing mechanism on compact imager